

Comando M170 OT

DESCRIZIONE DEL PRODOTTO

Comando manuale per la selezione delle mandate e la regolazione della pressione. Utilizzo su atomizzatori o gruppi irroranti. Regolazione della pressione precisa anche a bassa pressione. Corpo in ottone stampato. Posizioni di spruzzo selezionabili dall'operatore. Azionamento scorrevole con supporto camma in PTFE. Componenti ottimizzati per massima resistenza contro corrosione e usura. Funzionalità e durata assicurata dai materiali impiegati e dall'accuratezza del montaggio. Le versioni con valvole M172 dispongono di quattro mandate indipendenti.

CARATTERISTICHE TECNICHE E MATERIALI

Pressione di esercizio max.: 50bar

Portata max.: 150 l/min

Peso: **170.206.23** 4.2 kg - **170.206.23 KA/KM/KP/KR** 5.3 Kg

170.206.23 NU 3.9 kg -

170.206.23 PM/RG/RP 4.3 kg

170.206.23 SM/SR 4.1 kg

Materiali: ottone - sfere in AISI 304 - sedi in AISI 303 - materiali plastici ad alta resistenza - sede e pistone regolatore in acciaio inox con rivestimento anti usura - NBR - PTFE

AVVERTENZE

- L'installazione e la riparazione devono essere eseguite da personale qualificato dotato di attrezzature e strumenti di protezione idonei.

M170 OT Control Unit

PRODUCT DESCRIPTION

Manual control unit to select spraying sections and operating pressure on boom and air blast sprayers.

Precise and reliable pressure adjusting even at low pressures.

Forged brass body. Selects spraying positions. PTFE cam support for smooth spraying selection operations. Parts designed for maximum corrosion and wear resistance. Functionality and long life assured by materials used and fault proof manufacturing. Models with M172 valves has four independent outlets.

TECHNICAL FEATURES AND MATERIALS

Max operating pressure: 50 bar / 725 psi

Max capacity: 150 l/min - 40 USGal/min

Weight: **170.206.23** 4.2kg / 9.3lb

170.206.23 KA/KM/KP/KR 5.3kg / 11.7lb

170.206.23 NU 3.9kg/8.6lb - **170.206.23 PM/RG/RP**



4.3kg /9.5lb - **170.206.23 SM/SR** 4.1kg / 9.1lb

Materials: brass - AISI 304 balls - AISI 303 seats - high resistance plastic materials - stainless steel regulator piston and seat with wear proof coating - Buna N - PTFE

WARNINGS

- The installation and repair must be done by qualified technicians with suitable toolings and wearing suitable safety equipment.

SCHEMA DI IMPIEGO - OPERATING INSTRUCTIONS



CODICE code	A mm	B mm	C mm	D	E	KIT RICAMBIO spare parts kit
170.206.23	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 KA	180	285	25	G3/4M. - 3/4"BSPM.	4xG1/2M. - 4x1/2"BSPM	170.302.30 - 172.302.61
170.206.23 KM	180	285	25	G3/4M. - 3/4"BSPM.	4xG1/2M. - 4x1/2"BSPM	170.302.30 - 172.302.61
170.206.23 KP	180	285	25	G3/4M. - 3/4"BSPM.	4xG1/2M. - 4x1/2"BSPM	170.302.30 - 172.302.61
170.206.23 KR	180	285	25	G3/4M. - 3/4"BSPM.	4xG1/2M. - 4x1/2"BSPM	170.302.30 - 172.302.61
170.206.23 NU	150	240	G1M. - 1"BSPM	G3/4F. - 3/4"BSPF.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 PM	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 RG	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 RP	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 SM	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30
170.206.23 SR	180	285	25	G3/4M. - 3/4"BSPM.	2xG1/2M. - 2x1/2"BSPM	170.302.30

MANUTENZIONE E RIPARAZIONE

- Eseguire un ciclo di lavoro con acqua pulita alla fine di ogni utilizzo.
- Tutti gli interventi di **manutenzione straordinaria** e le riparazioni devono essere eseguite dal centro assistenza autorizzato dal costruttore o dall'installatore.

SMALTIMENTO



Questo prodotto non può essere smaltito come rifiuto domestico. Per ulteriori informazioni sullo smaltimento di questo apparecchio, contattare l'Ente della propria città o il servizio di smaltimento rifiuti. Il recupero dei materiali aiuterà a preservare le risorse naturali.

MAINTENANCE AND REPAIRS

- Flush the whole circuit with clean water after use.
- All operations of **extraordinary maintenance** and repairs must be carried out by specialized personnel from a service centre authorized by the manufacturer or the installer.

DISPOSAL AT THE END OF SERVICE

This product can not be disposed as household waste. For more information concerning the recycling of this product, please contact your waste disposal service. The recycling of materials will help to preserve the environment.



GARANZIA

I nostri prodotti sono controllati secondo campionamento statistico contro ogni difetto di produzione. La garanzia ha durata di 12 mesi dalla data di consegna con sostituzione o riparazione gratuita dei prodotti che presentino eventuali difetti di fabbricazione. Ci riserviamo la facoltà di ispezionare il prodotto, la sua installazione e di verificarne le modalità di impiego. I prodotti eventualmente difettosi devono essere ritornati franco di porto al vostro rivenditore. Non verranno riconosciute spese accessorie e qualsiasi altra richiesta di danni o indennizzi.

WARRANTY

Our products are inspected by MIL STD sampling against any manufacturing defects. The warranty is valid for 12 months from the date of delivery with replacement or repair free of charge of products having proven manufacturing faults. We reserve the right to inspect the returned products, to verify the installation and use. The faulty products must be returned to supplier freight prepaid. We will not refund any further expenses nor will accept any damage claims.

