





"TURBINE"



7.901.103



Standard con ugello M15x1 Ø2.3 - attacco G1/2M.

7.901.103 TG: standard con raccordo girevole G1/2M. - tracolla

Foro max. ugello: Ø3.5

Pressione di esercizio max.: 60 bar

Peso: 1.5 kg

Lunghezza: 600 mm

Materiali: ottone - acciaio inox - materiali plastici ad alta resistenza.

Impiego: trattamenti antiparassitari di colture a medio ed alto fusto. Lavaggio delle attrezzature agricole. Lavaggio industriale fino a 60°C. Nuovo design per corpo, impugnatura e protezione con riduzione del peso. Angolo di spruzzo regolabile con l'impugnatura anteriore che può contenere un ugello di ricambio. Nebulizzazione precisa, gittata, portata, robustezza e versatilità d'impiego. Ugello protetto dagli urti.

Standard with M15x1 spray tip Ø2.3 - 1/2" BSPM. connection

7.901.103 TG: standard with 1/2" BSPM swivel connection and shoulder belt

Max. spray tip hole: Ø3.5

Max operating pressure: 60 bar / 850 psi

Weight: 1.5 kg / 3.3 lb

Length: 600 mm / 26.5"

Materials: brass - stainless steel - high resistance plastic materials

Use: high pressure spraying and washing up to 140°F. Improved weight saving design for body, handles and protection. Front handle, for easy spray adjustment, can hold a spare spray tip. Accurate nebulization, long throw, flow rate, sturdiness and application versatility. Spray tip shock proof protection.

COME SI ORDINA / HOW TO ORDER

CODICE
code

7.901.103
7.901.103.TG



5
20

KIT
RICAMBIO
spare parts kit

7.302.1
7.302.1



PAGE 24



PAGE 20

