





M79



Standard completo di cavallotto, viti inox, membrana FPM, O Ring, ghiera G3/8, filtri a fessura - Ugelli non compresi

Pressione di esercizio max.: 30 bar

Apertura antigoccia: 1 bar

Peso: 270 g

Materiali: ottone nichelato - acciaio inox - NBR - PA66 - FPM

Impiego: su barre diserbanti. Ingombri ridotti. Due ugelli selezionabili con posizioni intermedie di chiusura. Eccellente resistenza alla pressione ed agli urti. Indicato per trattamenti che richiedono elevata penetrazione fogliare.

Standard with clamp, stainless steel screws, FKM diaphragm, O Ring, 3/8" BSP cap, slotted strainers - Spray tips not included

Max. operating pressure.: 30 bar / 450 psi


Antidrip opens at 1 bar / 15 psi

Weight: 270 g / 9.5 oz

Materials: nickel plated brass - stainless steel - Buna N - PA66 - FKM

Use: on crop protection booms. Compact. Rollover with two shut off positions. Pressure and shock proof. For high pressure on post emergence.

COME SI ORDINA / HOW TO ORDER

CODICE code	Ø1 mm	Ø2 mm	A mm	B mm	C mm	D mm		KIT RICAMBIO spare parts kit
79.617.3	1/2" (Ø21.3) - Ø22	Ø7	54	14.5	38	42	10	75.302.28



PAGE 78

UGELLI
TIPS

PAGE 87