



## MORSETTI - GETTI MORSETTO 1/2" CLAMPS - 1/2" CLAMP NOZZLES



267.612.177 (Ø22 1/2)  
267.612.1 (Ø20)



267.612.17 (Ø22 1/2)  
267.612.17 20 (Ø20)



267.612.178







267.612.18



265.612.176  
265.612.176 20



265.612.179



### Standard nichelati. Completi di viti inox e O Ring - Ugello non compreso

Pressione di esercizio max.: 50 bar

Peso: 267.612.1 65 g - 267.612.177 62 g - 267.612.17 70 g - 267.612.17 20 70 g -- 267.612.178 67 g - 267.612.18 75 g  
265.612.176 85 g - 265.612.176 20 83g - 265.612.179 93 g

**Materiali:** ottone nichelato - acciaio inox - NBR

**Impiego:** su atomizzatori e macchine per la protezione delle colture agricole in campo aperto. Leggeri e resistenti consentono il montaggio di getti, ugelli e manometri.

### Standard nickel plated. Stainless steel screws and O Ring - Spray tip not included

Max. operating pressure: 50 bar (725 psi)

Weight: 267.612.1 65 g (2.3 oz) - 267.612.177 62 g (2.2 oz) - 267.612.17 70 g (2.5 oz) - 267.612.17 20 70g (2.5 oz)  
267.612.178 67 g (2.4 oz) - 267.612.18 75 g (2.6 oz)  
265.612.176 85 g (3 oz) - 265.612.176 20 85 g (3 oz) - 265.612.179 93 g (3.3 oz)

**Materials:** nickel plated brass - stainless steel - Buna N

**Use:** for agriculture use on boom and air blast sprayers. Light and resistant. For nozzles, spray tips and pressure gauges.

### COME SI ORDINA / HOW TO ORDER

CODICE code	Ø1 mm	Ø2 mm	FILETTATURA thread	FILETTATURA CAVALLOTTO clamp thread	A mm	B mm	
267.612.1	Ø20			-	27.5		
267.612.177	Ø22 - Ø21.3			-	27.5		
267.612.17	Ø22 - Ø21.3			-	35		
267.612.17 20	Ø20	Ø7	G1/4F. 1/4" BSPF.	-	35	42	10
267.612.178	Ø22 - Ø21.3			M8	27.5		
267.612.18	Ø22 - Ø21.3			M8	35		
265.612.176	Ø22 - Ø21.3			-			
265.612.176 20	Ø20	Ø7	G3/8M. 3/8" BSPM.	-	38	42	10
265.612.179	Ø22 - Ø21.3			M8			



GETTI  
NOZZLES



UGELLI  
SPRAY TIPS



COMPONENTI  
PARTS



CATALOGHI  
CATALOGUES



RICAMBI  
SPARE PARTS :

265.612.176  
265.612.179