



SNODATI SWIVELS



264.612.167
264.612.170




264.612.168
264.612.173



264.612.171



264.612.172



Standard completi di ghiere G3/8 - Ugello non compreso

Pressione di esercizio max.: 20 bar

Peso: Singolo 67 g - Doppio 87 g

Materiali: ottone nichelato - acciaio inox - NBR - PA66 modificato all'urto

Impiego: in agricoltura per spruzzare insetticidi, fungicidi ed erbicidi. Impieghi industriali. Portaugelli orientabili in un arco di 270°. Le tenute con O Ring evitano la fuoriuscita del liquido durante il posizionamento del portaugello. I dadi bloccano la posizione scelta.

Standard with 3/8" BSP caps - Spray tip not included

Max. operating pressure.: 20 bar (290 psi)

Weight: Single 67 g (2.3 oz) - Double 87 g (3 oz)

Materials: nickel plated brass - stainless steel - Buna N - Shock resistance PA66

Use: for agriculture use. Insecticides, fungicides and weed control spraying. Industrial uses. Adjustable up to 270°. O Ring seals for drip proof adjustment. Two nuts to fix desired position.

COME SI ORDINA / HOW TO ORDER

CODICE code	VERSIONE model	ATTACCO connection	A mm	B mm	C mm	
264.612.167	Doppio - Double	1/4"NPTF.	26	36	-	10
264.612.168	Singolo - Single	1/4"NPTF.	26	36	-	
264.612.170	Doppio - Double	Ø12x19F.	26	36	-	
264.612.171	Doppio - Double	G1/4M. - 1/4"BSPM.	16	36	10	
264.612.172	Singolo - Single	G1/4M. - 1/4"BSPM.	16	36	10	
264.612.173	Singolo - Single	Ø12x19F.	26	36	-	



GETTI
NOZZLES



UGELLI
SPRAY TIPS



COMPONENTI
PARTS



CATALOGHI
CATALOGUES



RICAMBI
SPARE PARTS :

264.612.167
264.612.168
264.612.170

264.612.171
264.612.172
264.612.173