



# M201






**201.1915.3**  
12Vdc - 27w - 40 bar / 580 psi





**200.1915.4**  
12Vdc - 10w - 20 bar / 290 psi



**201.1915.3 SC**  
12Vdc - 27w - 40 bar / 580 psi

**200.1915.4 SC**  
12Vdc - 10w - 20 bar / 290 psi



CARATTERISTICHE TECNICHE / TECHNICAL FEATURES - 200.1915.3 - 200.1915.3 SC - 200.1915.3 NC										
 bar psi	 l/min-1bar USG pm-15psi	 12Vdc +-10%	A	B mm	C mm	D mm	F mm	G mm	Filtro strainer	 -10°C - +80°C
40 580	80 21	2A	G1/2F. 1/2"BSPM.	89.5	104	54	51.5	127	30 mesh	-10°C - +80°C
CARATTERISTICHE TECNICHE / TECHNICAL FEATURES - 200.1915.4 - 200.1915.4 SC - 200.1915.4 NC										
20 290	80 21	0.9A	G1/2F. 1/2"BSPM.	89.5	104	54	51.5	127	30 mesh	-10°C - +80°C



**Versioni con connettore: standard con LED di segnalazione valvola aperta**

<b>Versioni:</b>	<b>201.1915.3</b>	<b>bobina 27w - 40bar connettore DIN43650 A IP 67</b>	<b>cavo 1.5 m costampato</b>
	<b>201.1915.4</b>	<b>bobina 10w - 20bar connettore DIN43650 A IP 67</b>	<b>cavo 1.5 m costampato</b>
	<b>201.1915.3 SC</b>	<b>bobina 27w - 40bar connettore DIN43650 A - ISO4400 PG9 senza cavo</b>	
	<b>201.1915.4 SC</b>	<b>bobina 10w - 20bar connettore DIN43650 A - ISO4400 PG9 senza cavo</b>	
	<b>201.1915.3 NC</b>	<b>bobina 27W - 40 bar senza connettore e senza cavo</b>	
	<b>201.1915.4 NC</b>	<b>bobina 10W - 20 bar senza connettore e senza cavo</b>	

Pressione di esercizio max.: 201.1915.3 / 201.1915.3 SC / 201.1915.3 NC: 40 bar - 201.1915.4 / 201.1915.4 SC  
 201.1915.4 NC: 20 bar  
 Peso: 201.1915.3: 1.3 kg - 201.1915.3 SC: 1.1 kg 201.1915.3 NC 1.0 kg - 201.1915.4: 1.2 kg 201.1915.4 SC: 1.0 kg  
 201.1915.4 NC: 0,9 kg

**Materiali:** ottone - acciaio inox - tenute in FPM - materiali plastici ad alta resistenza

**Impiego:** su atomizzatori e gruppi irroranti. Applicazioni in campo industriale  
 - elettro valvola 12Vdc a solenoide normalmente chiusa (NC) servo azionata a membrana. Chiusura istantanea;  
 - bobina a basso assorbimento, orientabile, incapsulata (classe H - 180°) a servizio continuo con doppia tenuta in FPM;  
 - foro pilota e passaggi sovra dimensionati. Gruppo pilota in acciaio inox con trattamento nichel chimico e tenute in FPM;  
 - valvole da impiegare singolarmente in linea. Due connessioni di entrata e due di mandata configurabili

**Models with connector : open valve warning LED**

<b>Models:</b>	<b>201.1915.3</b>	<b>27w coil - 40bar (580 psi) DIN43650 A IP 67 connector 1.5m integrated moulded cable 2 poles + ground</b>
	<b>201.1915.4</b>	<b>10w coil - 20 bar (290 psi) DIN43650 A IP 67 connector 1.5m integrated moulded cable 2 poles + ground</b>
	<b>201.1915.3 SC</b>	<b>27w coil - 40bar (580 psi) DIN43650 A - ISO4400 PG9 connector without cable</b>
	<b>201.1915.4 SC</b>	<b>10w coil - 20bar (290 psi) DIN43650 A - ISO4400 PG9 connector without cable</b>
	<b>201.1915.3 NC</b>	<b>27w coil - 40 bar (580 psi) without connector and cable</b>
	<b>201.1915.4 NC</b>	<b>10w coil - 20 bar (290 psi) without connector and cable</b>

Max. operating pressure: 201.1915.3 / 201.1915.3 SC /201.1915.3 NC: 40 bar / 580 psi - 201.1915.4 / 201.1915.4 SC  
 201.1915.4 NC: 20 bar / 290 psi  
 Weight: 201.1915.3: 1.3 kg / 2.9 lb - 201.1915.3 SC: 1.1 kg / 2.4 lb - 201.1915.3 NC: 1.0 kg / 2.2 lb - 201.1915.4: 1.2 kg  
 2.7 lb - 201.1915.4 SC : 1.0 kg / 2.2 lb - 201.1915.4 NC: 0,9 kg / 2 lb

**Materials:** brass - stainless steel - FKM seals - high resistance plastic materials

**Use:** on airblast sprayers. Industrial applications  
 - normally closed (NC) 12Vdc servo operated diaphragm solenoid valve. Instantaneous shut-off;  
 - low power consumption continuous duty incapsulated revolving coil (H class 180°) with double FKM seal;  
 - oversized pilot and internal holes. Niploy processed stainless steel pilot unit with FKM seal;  
 - single unit line use. Two inlets and two outlets.

**COME SI ORDINA / HOW TO ORDER**

<b>CODICE</b> <small>code</small>	<b>VERSIONE</b> <small>model</small>	<b>CONNETTORE</b> <small>connector</small>	<b>COMPLETO DI CAVO</b> <small>cable supplied</small>	<b>KIT RICAMBIO</b> <small>spare parts kit</small>
<b>201.1915.3</b>	27W - 40bar / 580 psi	DIN 43650 A - IP67	Costampato Integrated moulded	200.302.46
<b>201.1915.4</b>	10W - 20bar / 290 psi	DIN 43650 A - IP67	Costampato Integrated moulded	200.302.46
<b>201.1915.3 SC</b>	27W - 40bar / 580 psi	DIN 43650 A ISO 4400 PG9	NO	200.302.46
<b>201.1915.4 SC</b>	10W - 20bar / 290 psi	DIN 43650 A ISO 4400 PG9	NO	200.302.46
<b>201.1915.3 NC</b>	27W - 40bar / 580 psi	NO	NO	200.302.46
<b>201.1915.4 NC</b>	10W - 20bar / 290 psi	NO	NO	200.302.46