


**MORSETTI / CLAMPS**267.612.177 (Ø22 1/2)
267.612.1 (Ø20)267.612.17 (Ø22 1/2)
267.612.17 20 (Ø20)

267.612.178



267.612.18

**Standard nichelati - completi di viti inox e O Ring**

Pressione di esercizio max.: 50 bar

Peso: 267.612.1 65 g - 267.612.177 62 g - 267.612.17 20 70 g - 267.612.17 70 g - 267.612.178 67 g - 267.612.18 75 g

Materiali: ottone nichelato - acciaio inox - NBR**Impiego:** su gruppi da diserbo ed atomizzatori. Leggeri e resistenti consentono il montaggio di getti, ugelli e manometri.**Standard nickel plated with stainless steel screws and O Ring**

Max. operating pressure: 50 bar / 725 psi

Weight: 267.612.177 62 g / 2.2 oz - 267.612.17 70 g / 2.5 oz - 267.612.178 67 g / 2.4 oz - 267.612.18 75 g / 2.6 oz - 267.612.1 65 g / 2.29 oz - 267.612.17 20 g / 2.47 oz

Materials: nickel plated brass - stainless steel - Buna N**Use:** on booms and air blast sprayers. Light and resistant. For nozzles, spray tips and pressure gauges.**COME SI ORDINA / HOW TO ORDER**

CODICE code	Ø1 mm	Ø2 mm	FILETTATURA thread	FILETTATURA CAVALLOTTO clamp thread	A mm	B mm	
267.612.1	Ø20	Ø7		-	25	42	25
267.612.177	Ø22 - Ø21.3	Ø7		-	25		
267.612.17	Ø22 - Ø21.3	Ø7		-	34.5		
267.612.17 20	Ø20	Ø7	G1/4F.	-	34.5		
267.612.178	Ø22 - Ø21.3	Ø7	1/4"BSPP.	M8	25		
267.612.18	Ø22 - Ø21.3	Ø7		M8	34.5		