



# ALBUZ® AVI 110°





**ALBUZ**  
ITALIAN EXCLUSIVE DISTRIBUTOR



300.618.5 EPDM  
300.618.6 FPM/FKM



◀ PAGE 08/43 ▶



Da 30 a 50 bar  
From 40 to 70 psi



Disponibili in ALBUZ® blister (8 ugelli) - COME SI ORDINA: BL+codice ugello  
**Materiali:** materiali plastici ad alta resistenza - allumina. **Impiego:** tutti i trattamenti con prodotti sistemici, a contatto e fertilizzanti liquidi. Ugello anti deriva ad iniezione d'aria. Dimensioni compatte (27 mm). Distribuzione eccellente in un ampio arco di pressioni. Altezza barra minima consigliata: 50/60 cm. Pressione consigliata 3.0 bar - **Confezioni da: 50 - 8 (blister)**

ALBUZ® blister available (8 spray tips) - HOW TO ORDER: BL+spray tip code  
**Materials:** high resistance plastic materials - ceramic. **Use:** all applications including liquid fertilizers on boom sprayers. Anti drift air injection spray tip. Compact design (27 mm). Excellent spray distribution over a wide range of pressures. Minimum recommended boom height: 50/60cm (20"/24"). 3.0 bar (40 psi) recommended operating pressure. **Pieces per box: 50 - 8 (blister)**

FILTRO	COME SI ORDINA	bar	l/min	VELOCITÀ km/h					
				6	8	10	12	14	16
100 MESH	228.1801.10 (11001) ARANCIO	3	0.40	80	60	48	40	34	30
		4	0.46	92	69	55	46	39	35
		5	0.52	104	78	62	52	45	39
100 MESH	228.1801.41 (110015) VERDE	3	0.60	120	90	72	60	51	45
		4	0.69	138	104	83	69	59	52
		5	0.77	154	116	92	77	66	58
100 MESH	228.1801.42 (11002) GIALLO	3	0.80	160	120	96	80	69	60
		4	0.92	184	138	110	92	79	69
		5	1.03	206	155	124	103	88	77
50 MESH	228.1801.43 (110025) LILLA	3	1.00	200	150	120	100	86	75
		4	1.15	230	173	138	115	99	86
		5	1.29	258	194	155	129	111	97
50 MESH	228.1801.44 (11003) BLU	3	1.20	240	180	144	120	103	90
		4	1.39	278	209	167	139	119	104
		5	1.55	310	233	186	155	133	116
50 MESH	228.1801.45 (11004) ROSSO	3	1.60	320	240	192	160	137	120
		4	1.85	370	278	222	185	159	139
		5	2.07	414	311	248	207	177	155
50 MESH	228.1801.46 (11005) MARRONE	3	2.00	400	300	240	200	171	150
		4	2.31	462	347	277	231	198	173
		5	2.58	516	387	310	258	221	194
50 MESH	228.1801.47 (11006) GRIGIO	3	2.40	480	360	288	240	206	180
		4	2.77	554	416	332	277	237	208
		5	3.10	620	465	372	310	266	233
50 MESH	228.1801.8 (11008) BIANCO	3	3.20	640	480	384	320	274	240
		4	3.70	740	555	444	370	317	278
		5	4.13	826	620	496	413	354	310
50 MESH	228.1801.11 (11010) AZZURRO	3	4.00	800	600	480	400	342	300
		4	4.62	924	693	554	462	396	347
		5	5.16	1032	774	619	516	442	387

STRAINER	HOW TO ORDER	psi	USGal min	SPEED mph					
				4	5	6	7	8	10
100 MESH	228.1801.10 (11001) ORANGE	40	0.100	7.4	5.9	5.0	4.2	3.7	3.0
		60	0.122	9.1	7.2	6.0	5.2	4.5	3.6
		70	0.132	9.8	7.8	6.5	5.6	4.9	3.9
100 MESH	228.1801.41 (110015) GREEN	40	0.150	11.1	8.9	7.4	6.4	5.6	4.5
		60	0.184	13.4	10.7	8.9	7.6	6.8	5.5
		70	0.200	14.9	11.9	9.9	8.5	7.4	5.9
100 MESH	228.1801.42 (11002) YELLOW	40	0.200	14.9	11.9	9.9	8.5	7.4	5.9
		60	0.245	18.2	14.6	12.1	10.4	9.1	7.3
		70	0.265	19.7	15.7	13.1	11.2	9.8	7.9
50 MESH	228.1801.43 (110025) LILAC	40	0.250	18.6	14.9	12.4	10.6	9.3	7.4
		60	0.306	20.8	16.6	13.9	11.9	10.4	8.3
		70	0.331	24.6	19.7	16.4	14.0	12.3	9.8
50 MESH	228.1801.44 (11003) BLUE	40	0.300	22.3	18.1	14.9	12.7	11.1	8.9
		60	0.367	27.3	21.8	18.2	15.6	13.6	10.9
		70	0.397	29.5	23.6	19.7	16.8	14.7	11.8
50 MESH	228.1801.45 (11004) RED	40	0.400	29.7	23.8	19.8	17.0	14.9	11.9
		60	0.490	36.4	29.1	24.3	20.8	18.2	14.6
		70	0.529	39.3	31.4	26.2	22.5	19.6	15.7
50 MESH	228.1801.46 (11005) BROWN	40	0.500	37.1	29.7	24.8	21.2	18.6	14.9
		60	0.612	45.4	36.4	30.3	26.0	22.7	18.2
		70	0.661	49.1	39.3	31.7	28.1	24.5	19.6
50 MESH	228.1801.47 (11006) GREY	40	0.600	44.6	35.6	29.7	25.5	22.3	17.8
		60	0.735	54.6	43.7	36.4	31.2	27.3	21.8
		70	0.794	59.0	47.2	39.3	33.7	29.5	23.6
50 MESH	228.1801.8 (11008) WHITE	40	0.81	60.1	48.1	40.1	34.4	30.0	24.1
		60	0.99	73.5	58.8	49.0	42.0	36.8	29.4
		70	1.07	79.5	63.6	53.0	45.4	39.7	31.8
50 MESH	228.1801.11 (11010) BLACK LIGHT BLUE	40	1.00	74.3	59.4	49.5	42.4	37.1	29.7
		60	1.14	84.6	67.7	56.4	48.3	42.3	33.9
		70	1.32	98.0	78.4	65.3	56.0	49.0	39.2

